

Chemical/Biological Protection For Law Enforcement & Emergency Responders





· Bromobutyl rubber resists chemical attack; no need for second skin

· Comfortable 6-strap fabric harness fits under ballistic helmets

• Fits into standard gas mask pouches worn on the leg, belt or vest

M-TAC RESPIRATOR

Chemical/Biological Protection For Law Enforcement & Emergency Responders

Cartridge Testing Conditions and Results - Chemical Warfare Agents

| Challenge Agent | Test Concentration | Flow Rate | Breakthrough Concentration | Time to Breakthrough |
|-------------------------|------------------------|-----------|-------------------------------|-------------------------|
| DMMP (surrogate for GB) | 3000 mg/m ³ | 50 lpm | 0.04 mg/m ³ | >210 minutes* |
| Sarin (GB) | 4000 mg/m³ | 32 lpm | 0.04 mg/m ³ | >215 minutes* |
| Cyanogen Chloride (CK) | 4000 mg/m ³ | 32 lpm | 8.0 mg/m³ | 30 minutes* |
| Chloropicrin (PS) | 15000 mg/m³ | 30 lpm | 0.7 mg/m ³ | 70 minutes |
| Hydrogen Cyanide (AC) | 5500 mg/m³ | 30 lpm | 5.0 mg/m³ | 45 minutes |

Shelf Life: 10 years (foil wrap, plugs)

Diameter: 4.25 inches (10.8 cm)

Height: 3 inches (7.6 cm)
Weight: 0.71 pounds (323 grams)
Connection: 40 mm NATO thread
Body Material: Black polyamide

The Cartridge was tested by independent labs to verify its performance against a range of chemical warfare agents.

Cartridge Testing Conditions and Results - NIOSH 42 CFR Part 84 Gases (Toxic Industrial Materials)

| Gas Challenge | Test Concentration | Flow Rate | Breakthrough Concentration | Time to Breakthrough |
|-------------------|-----------------------|-----------|-------------------------------|-------------------------|
| Phosphine | 1500 ppm | 64 lpm | 0.3 ppm | >24 minutes** |
| Tear Gas (CS) | 3 ppm | 64 lpm | 0.05 ppm | >480 minutes** |
| Tear Gas (CN) | 16 ppm | 64 lpm | 0.05 ppm | >480 minutes** |
| Chlorine | 500 ppm | 64 lpm | 5.0 ppm | >35 minutes** |
| Hydrogen Chloride | 500 ppm | 64 lpm | 5.0 ppm | 25 minutes** |
| Sulfur Dioxide | 500 ppm | 64 lpm | 5.0 ppm | >85 minutes** |
| Formaldehyde | 100 ppm | 64 lpm | I.0 ppm | >100 minutes** |
| Ammonia | 1000 ppm | 64 lpm | 50.0 ppm | >55 minutes** |
| Methylamine | 1000 ppm | 64 lpm | 10.0 ppm | >80 minutes** |
| Hydrogen Sulfide | 1000 ppm | 64 lpm | 10.0 ppm | >60 minutes** |
| Chlorine Dioxide | 500 ppm | 64 lpm | 0.1 ppm | >60 minutes** |
| Hydrogen Fluoride | 70 ppm | 64 lpm | 3.0 ppm | >60 minutes** |

^{*} Note: These tests are part of the performance specifications for the C2A1 canister, as specified in military specification MIL-PRF-51560A (EA), 1 July 1997, Performance Specification: Canister, Chemical-Biological Mask: C2A1. The Cartridge meets or exceeds the performance requirements of the C2A1 canister for these gases.

In addition to protecting against toxic industrial materials (TIMs) and the chemical warfare agents listed above, the Cartridge offers particulate protection that is over 99.97% efficient. The PI00 filter removes all aerosols and solid particulates, which makes it effective protection against a range of weaponized biological agents.

| Product Code | Description | |
|--------------|---|--|
| 59200-00001 | AOSafety M-Tac Respirator, Small | |
| 59201-00001 | AOSafety M-Tac Respirator; Medium | |
| 59202-00001 | AOSafety M-Tac Respirator, Large | |
| 59231-00000 | AOSafety M-Tac Cartridge | |
| 59212-00000 | Maintenance Kit | |
| 59213-00000 | Head Harness | |
| 59215-00000 | Storage/Carrying Case | |
| 59216-00000 | Speech Capsule | |
| 59217-00000 | Spectacle Kit | |
| 59219-00000 | Bottle Cap and Bottle for Drinking Tube | |



For ordering information or your nearest stocking distributor:

U.S.A Canada Export Sales
Phone: I-800-225-9038 I-800-387-9681 I-317-692-6643
Fax: I-800-488-8007 I-800-488-8007 I-317-656-5827

Technical Questions?

U.S.A & Canada Other Countries

Phone: I-800-444-4774 I-508-764-572 I

Fax: I-508-764-5640 I-508-764-5640

^{**} Note: The Cartridge toxic industrial materials (TIMs) performance exceeds the 42 CFR Part 84 minimum service life requirements for these gases.